MiniMix® 100 CC

Lab blender

interscience

Simple, Accurate,Space-saving

The most compact blender in the world, BagMixer® 100 MiniMix is available in Click & Clean® version!

MiniMix® 100 automatically blends any solid sample in a sterile bag and allows safe and easy extraction of bacteria. You can pipet and analyse the filtrate without any risk of alteration or cross contamination. **This is the safest and most economical sample preparation method.**

MiniMix® 100 CC incorporates the **Click & Clean®** and side-by-side paddle stopping systems, already highly acclaimed on **BagMixer® 400 CC** and the **adjustable blending strength** system.

1 Multifunction screen

For easy control of the blending parameters



Blending time

Blending speed

2 Q-Tight® system

A special closing system that avoids every risk of leaking.



Leak-tight

3 Adjustable blending strength PATENTED

You can adapt the blending chamber to the size of the sample to get OPTIMAL EXTRACTION!



Small sample : Move the paddles forward

Large sample : Move the paddles backward

4 Click & Clean® system PATENTED

UNIQUE! TOTAL CLEANING of the blendin chamber is possible!



Click off



Clean



Click back on

5 Side-by-side paddle stop PATENTED



For easy and fast insertion of your sterile bags in the blender.

Advantages

- *Compact, silent*
- *User friendly*
- *Optimal extraction*
- *Lifetime warranty on window door and shock absorbers*
- *Stainless steel*
- *Q-Tight®: Leak-tight*
- *Easy and total cleaning*

Applications

- Food microbiology
- Pharmaceutical
- Veterinary, clinical (biopsies, organ sampling...)
- Molecular extraction (proteins, lipids, DNA...)
- Toxin research (HPLC, GCMS...)

Specifications

- Useful capacity: 5-100 mL
- For samples: 0.5 g - 10 g
- Adjustable time: 1 s to 59 mn. countdown & open running (∞)
- Speed calibrated by microprocessor (3 - 12 strokes/s)
- Side by side paddle stop
- Q-Tight® seal: thickness of 12mm

- Stainless steel
- Drip tray
- Adjustable blending power
- Click & Clean® system: removable & autoclavable paddles
- Multifunction screen
- Lifetime warranty on window door & shock absorbers

- Pwr.: 110 / 220 V ~ 50 - 60 Hz
- Dim. (w x d x h): 21 x 37 x 20 cm
- Net weight: 13 Kg

Ref : 013 230

ISO 6887-1 | ISO 7218 | FDA BAM Bacteriological Analytical Manual | ISO 9001 2008 | WEEE 2002/96/EC | RoHS 2002/95/EC

Also available

MiniMix® 100 P CC

- Variable blending speed (3-12 strokes/s)
- Variable blending time (1 - 1h or ∞)
- Available in CoolMix® version

BagPage® 80 & 100

Full page sterile filter bags

Robust & food compatible, multilayer.

BagLight® 100

Plain sterile bags

Made of PolySilk®, extremely robust. For samples that do not require any filtration.

BagOpen® 100

Bag opener

Easy opening, extremely stable. Resistant to cleaning agents.

Get the best results with

DiluFlow®

Gravimetric dilutor

Automatically dilutes with the appropriate mass of solvant.

BagClip® 100

Closing clips

100% watertight & waperproof, closes any kind of bag.

RollBag®

Sampling bag

For collecting, sampling & preservation of any sample. Stands up alone.

BagRack® 100

Storage rack

Stainless steel, autoclavable.

Discover our complete range for microbiology

BagFilter®
Sterile bags

DiluFlow®
Gravimetric dilutors

FlexiPump®
Peristaltic pumps

easySpiral Dilute®
Serial dilutors and platers

Scan®
Colony counters

Distributor

www.interscience.com

interscience **INTERNATIONAL**
30, ch. Bois Arpents - 78860 St Nom - FRANCE
T: +33 (0)1 34 62 62 61 - F: +33 (0)1 34 62 43 03
E-mail: info@interscience.com

interscience **USA & CANADA**
199 Weymouth ST. - ROCKLAND - MA 02370 - USA
T: +1 781 792 2133 - F: +1 781 792 2134
E-mail: sales.usa@interscience.com

interscience **CHINA**
上海市徐汇区吴兴路277号锦都大厦718室-200030
电话: +86 (0)21-64739390 - +86 189 3097 0733
邮 址: sales.china@interscience.com

MiniMix_B_0615. Pictures and informations in this brochure are not contractually binding. MiniMix®, BagMixer®, DiluFlow®, FlexiPump®, easySpiral Dilute®, Scan®, BagPage®, BagLight®, BagOpen®, BagRack®, BagClip® are trademarks. This document is the translation of the french brochure and is not contractually binding. INTERSCIENCE reserves the right to change or improve the specifications of its products without notice. Please visit www.interscience.fr for current updates and additional information. RCS 950 356 220 Versailles. INTERSCIENCE SARL F78860.

EN