

# Temperature Performance Eppendorf ThermoMixer® C with individual Eppendorf SmartBlocks

With the new generation of Eppendorf ThermoMixer individual data regarding the temperature performance are available for each Eppendorf SmartBlock. Detailed specifications are listed below:

## Eppendorf ThermoMixer® C with Eppendorf SmartBlock

	0.5 ml	1.5 ml	2.0 ml	cryo	12 mm	PCR 96	PCR 384	Plates	5 ml	15 ml	50 ml
<b>Minimum temperature below ambient temperature</b>	max. 15 °C						max. 13 °C				
<b>Max. temperature accuracy 20–45 °C</b>	+/- 0.5 °C						+/- 1 °C				
<b>Max. temperature accuracy &lt;20 °C and &gt;45 °C</b>	+/- 1 °C						+/- 4 °C				
<b>Max. temperature homogeneity 20–45 °C</b>	+/- 0.5 °C										
<b>Max. homogeneity &lt;20°C or &gt;45°C</b>	+/- 1 °C						+/- 2 °C				
<b>Max. heating rate (in °C/min)</b>	6 °C						7 °C	5.5 °C	4 °C		
<b>Max. cooling rate above ambient temperature (in °C/min)</b>	2.5 °C						3 °C	2 °C			
<b>Max. cooling rate below ambient temperature (in °C/min)</b>	0.8 °C						1 °C	0.5 °C	0.3 °C		

Your local distributor: [www.eppendorf.com/contact](http://www.eppendorf.com/contact)  
Eppendorf AG · 22331 Hamburg · Germany  
[eppendorf@eppendorf.com](mailto:eppendorf@eppendorf.com) · [www.eppendorf.com](http://www.eppendorf.com)

[www.eppendorf.com](http://www.eppendorf.com)