LGUex 1500

MediLine

Total gross capacity	139 litre
Ext. dimensions in mm (w/d/h)	600/615/820
Int. dimensions in mm (w/d/h)	454/450/663
Energy consumption in 24 h	0,926 kWh
Climate rating[1]	SN-ST
Cooling system	static
Defrosting	manual
Temperature range	-9°C to -26°C
Gastronorm	–
Housing material/colour	steel/white
Door/lid material	Steel
Liner Material	moulded polystyrol white
Type of control	electronic controller
Temperature display	external digital
Interior light	–
Fault: warning signal	visual and audible
Interface	RS 485
volt-free alarm contact	yes
Shelves	4
Adjustable Shelving	–
Number of drawers	3
Number of baskets	4
Maximum number of baskets	–
Shelf material	evaporator plates
Shelf loading	24 kg
Height of adjustable legs	-
Castors/type of castors	–
Door handle	Ergonomic door handle
Foot pedal opener	–
Self-closing door	yes
Insulation	55 - 55 mm
Defrost water drain	–
Refrigerant	R 600a
Airborne acoustical noise emissions	45 dB(A)
Gross/net weight	44/42 kg
EAN-Nr.	9005382171011

Subject to modification. Timestamp: 22.03.2016

1 Climate Ratings: **SN** +10°C to +32°C **N** +16°C to +32°C **ST** +16°C to +38°C **T** +16°C to +43°C

LIEBHERR